

# Object - authentication3DSecure

The elements contain the 3Dsecure information of the transaction

Type: request to Payline

| Field                | Description                                                                                              | Required | Format | Condition                                 |
|----------------------|----------------------------------------------------------------------------------------------------------|----------|--------|-------------------------------------------|
| md                   | 3DSecure merchant data : Referred to POST by ACS                                                         | No       | AN20   |                                           |
| pares                | Payer authentication response : Referred to POST by ACS                                                  | No       | AN     |                                           |
| xid                  | Unique transaction identifier, base-64 encoded                                                           | No       | AN28   |                                           |
| eci                  | Electronic Commerce Indicator. to send in the authorization                                              | No       | AN2    |                                           |
| cavv                 | Cardholder Authentication Verification Value determined by the ACS.                                      | No       | AN28   |                                           |
| cavvAlgorithm        | Algorithm used for CAVV generation. The current possible values are: <a href="#">Codes cavvAlgorithm</a> | No       | N1     | W : Wallet UEP                            |
| vadsResult           | Summary of 3DSecure operations in hexadecimal. This field is no longer used.                             | No       | AN8    |                                           |
| typeSecurisation     | Field used as information for authentication.This field is no longer used.                               | No       | AN10   | 20 : VADS<br>else 9 : VAD                 |
| PaResStatus          | To use a non-Payline MPI, you must fill in this field. See values : <a href="#">Codes PaResStatus</a>    | No       | AN1    | Provided Version 27 in response services. |
| VeResStatus          | To use a non-Payline MPI, you must fill in this field. See values : <a href="#">Codes VeResStatus</a>    | No       | AN1    | Provided Version 27 in response services. |
| resultContainer      | Container gathering the authentication result parameters.                                                | No       | AN2048 | Version 21 or higher (3DSV2)              |
| authenticationResult | NOT USED                                                                                                 |          |        |                                           |