

# Webservice - getTransactionDetailsRequest

Request	Response
---------	----------

The search function of a transaction permits to obtain the details of a payment transaction whatever its state.  
The getTransactionDetailsRequest message is used to search the details of a payment transaction.  
The query has the following structure.

 **We recommend to use transactionID to identify a unique transaction.** For specific case, you can use orderRef to identify the transaction, but you have to be sure, there is only one operation to do not get any error. 

## Request

Element	Description	Required	Format
version	Payline web services version. To be valued with the latest version: <a href="#">see the table of versions</a> .	Yes	N2
transactionid	The identifier of the transaction communicated by Payline.	No	AN50
orderRef	The identifier of the order at the merchant.	No	AN50
startDate	Start of the period for which transactions are sought. Format DD/MM/YYYY.	No	Date
endDate	End of the period for which transactions are sought. Format DD/MM/YYYY.	No	Date
transactionHistory	This flag retrieves the list of associated payments (associatedTransactions) as well as the status history (statusHistoryList) for a given transaction.  This feature is optional. The possible values are: - "Y": display of the status history and associated payments; - "N": absence of status history and associated payments; - Null or unspecified: absence of status history.	No	A1
archiveSearch	True: The search in the archive database will be activated. False: The search in the archive database will not be activated.	No	Boolean