

Object - sdkChallenge

The merchant receives the SDK Challenge from authentication request.

Field	Description	Required	Format	Condition
cardType	Card type: CB, VISA, MASTERCARD, MAESTRO, AMEX	N	AN20	Version 31 or higher (3DSV2)
threeDSServerTransID	Required by the SDK to continue in challenge. Canonical format as defined in IETF RFC 4122. Example = 6bf8f23c-e721-5bfc-8000-00000039a43d	N	AN36	
threeDSVersion	This field contains the 3DS version that was used to process the transaction. Example = 2.2.0	N	AN8	
authenticationType	Indicates the type of authentication that will be used to challenge the card holder. Possible Values: 01 - Static 02 - Dynamic 03 - OOB (Out of Band) 04 - Decoupled	N	AN2	
transStatus	Returns an indicator about enrollment result : see values transStatus.	N	AN1	
sdkTransID	Universally unique transaction identifier assigned by the 3DS SDK to identify a single transaction. Canonical format as defined in IETF RFC 4122. Example = b60c9879-ac77-4918-a317-7b01c4317053	N	AN36	
dsTransID	Canonical format as defined in IETF RFC 4122. May utilise any of the specified versions as long as the output meets specified requirements.	N	AN36	
acsTransID	Required by the SDK to continue in challenge. Canonical format as defined in IETF RFC 4122. Example = 38b4a4f4-ceee-457a-80d3-40d4fd3aa618	N	AN36	
acsRenderingType	Example = { "acsInterface" : "01", "acsUiTemplate" : "01" }	N	JSON	
acsReferenceNumber	Required by the SDK to continue in challenge. Example = 3DS_LOA_ACS_MOMD_020100_00061	N	AN32	
acsSignedContent	Required by the SDK to continue in challenge. Example = eyJ4NWMi###6716..##95_fYwXQ	N	CDA TA	
acsOperatorID	Any individual DS may impose specific formatting and character requirements on the contents of this field.	N	AN32	
acsChallengeMandated	Example = N	N	AN1	